

30X RGBlink vue PTZ camera



Front View



Rear View



Front View (Support NDI)

Key Features

- High speed optical zoom
 - Low-Latency SRT Upload to Cloud
 - High performance in low light scenarios with Wide Dynamic Range
 - Full 1920×1080p HD Resolutions up to 60 frames per second
 - H.265/H.264 Dual Stream Output Adapted to Different Network Environments
 - Pan and Tilt Control
- Optional interface
 - NDI | HX output optional
 - Wide Application
 - Low-power Sleep Function
 - Support TALLY
 - Support PoE

Specification

Interface	Output	3G SDI HDMI USB LAN	1xBNC 1xHDMI-A 1xUSB-A 1xRJ45
	Audio	IN	1x3.5mm Stereo Jack
	Control	RS232 IN/OUT RS485	2xDIN8 1x4pin Terminal
	Power		1xDC12V Jack
	Camera	30X Optical Zoom f= 5.2~148.4mm View Angle 2.14°~58.1° AV F1.3 ~ F4.8 Digital Zoom 10X Minimum Illumination 0.5Lux (F1.8, AGC ON) DNR 2D & 3D DNR White Balance Auto/Manual/One Push/3000K to 7000K(selectable) Focus Auto/Manual Aperture/Electronic Shutter Auto/Manual BLC ON/OFF WDR OFF/Dynamic Level Adjustment Video Adjustment Brightness/Color/Saturation/Contrast/Sharpness/B/W mode/Gamma curve SNR >55dB Effective Pixels 2.07 mega-pixel Sensor 1/2.8 inch HD CMOS	
Performance	Pan-and-Tilt Parameter	Pan/Tilt Movement Pan/Tilt Control Speed Preset Speed/Quantity 360° TALLY	-170°~+170°/-30°~+90° 0.1~60°/S; 0.1~30°/S Pan:60°/S, Tilt:30°/S; Up to 255 preset positions (10 remote control) full 360° view of TALLY
	Audio Compression Format	AAC MP3 G.711A	
	Video Compression Format	H.264 H.265 Dual Streaming Output	
	Output Resolutions	1080p60/59.94/50/30/29.97/25 1080i60/59.94/50 720p60/59.94/50	
	Control Protocol	VISCA Pelco-D Pelco-P ONVIF	
	Baud Rate(bps)	115200 9600 4800 2400bps	
	Network Protocol	RTSP RTMP ONVIF	
	Supported Standards	SDI SMPTE 425M (Level A & B) SMPTE 424M SMPTE 292M SMPTE 259M-C DVB-ASI	
	Power	Input Voltage DC12V/1.5A Max Power 12W	
	Environment	Temperature -10℃~50℃ Humidity 20%~80%	
Physical	Weight	Net 1.7kg	
	Dimension	Net 180mm(front)×188mm(side)×198mm(height)	

Order Codes

Product Code	Item
981-0011-33-0	RGB30X-POE-TLY
981-0011-34-0	RGB30X-PNDI-TLY

Tel: +86-592-5771197 | Fax: +86-592-5788216 | E-mail: sales@rgbblink.com
Headquarter: Room 601A, No. 37-3 Banshang community, Building 3, Xinke Plaza, Torch Hi-Tech Industrial Development Zone, Xiamen, China
Specifications are correct at time of printing and subject to change or alteration without notice.

